

NEW

axtar **XXL**<sup>®</sup>

THE XXL INNOVATIVE SOLUTION FOR PATIENT  
WITH PRESSURES ULCERS OR WITH HIGH RISK



PREVENTION OF **MEDIUM TO HIGH** PRESSURE ULCER RISKS

PATIENT BEDRIDDEN FROM **10 TO 15 HOURS A DAY**

PATIENT WEIGHT: **100 TO 270 KG**

2 WIDTHS: **120 CM OR 140 CM**

WINCARE  
g r o u p

# axtar<sup>®</sup> XXL




## PUMP

- ▶ Patented system of automatic and continuous calculation of inflation pressure according to patient's morphology
- ▶ Technology based on alternating pressure 1 cell in 2
- ▶ 3 modes: dynamic, static low pressure, care
- ▶ Comfort settings: customization of comfort and seating position adjustment
- ▶ Visual and audible alarms
- ▶ Compatible AIRCARE program


## QR Code for a simple and quick access to product informations

- ▶ Product item and serial number
- ▶ Leaflet, technical description, Userguide, FAQ, Autotest



### SIDE CPR (CARDIO PULMONARY RESCUE)

- ▶ to deflate the mattress in less than 15 seconds



### HOUSSE PROMUST PU HD

- ▶ Upper side: Stretchable, breathable, impermeable to liquids and permeable to vapor
- ▶ Lower side: non-slip base



### FIRM EDGE

- ▶ For good stability when lifting and transferring



Delivered in a transport bag

CE



AirCare®  
PROGRAM  
COMPATIBLE



### 4 THERAPEUTIC AREAS:

- ▶ 2 static head cells
- ▶ 4 cervico-dorsal cells
- ▶ 10 cells around the sacrum area with an air base to ensure stability
- ▶ 5 heels cells with independent and available pressure relief



### BOUCHON DE TRANSPORT

- ▶ Transport plug: System for opening and sharing 2 air channels (autonomy of 8 hours)



### CELLS

- ▶ 21 removable and independant Polyuréthane Ether cells of 20 cm therapeutic AIR

# THE **plus** PRODUCT

## **plus** THERAPEUTIC EFFECTIVENESS

- ▶ Management of the sitting position
- ▶ Automatic and continuous calculation of inflation pressure
- ▶ Heel-position load releases as standard
- ▶ 2 therapeutical mode : static low pressure or alternating (1 cells to 2)

## **plus** EASY-TO-USE

- ▶ Intuitive compressor interface
- ▶ Simplified operating instructions for the compressor
- ▶ Technical diagnostic assistance with QR code
- ▶ Nursing mode for caregivers

## **plus** CONFORTABLE

- ▶ Comfort adjustment whatever the mode used or the position of the patient
- ▶ 2 widths available
- ▶ Firm edge for good stability when lifting and transferring

## **plus** SAFETY

- ▶ Automatic keyboard lock
- ▶ Cable bushing optiona

## **plus** ECO-FRIENDLY

- ▶ Eco-design process

# TECHNICAL CARACTETISTICS

DESCRIPTION	REFERENCE	DIMENSIONS	PATIENT WEIGHT	FIRE STANDARDS	KEY FEATURE
<b>axtar<sup>®</sup> XXL</b> (pump + overlay) <b>Promust PU HD cover</b> <b>For 120cm wode bed</b>	VAXT/XXL-120	195 x 117 x 20.5 cm	100 to 270 Kg	EN 597-1 & 2 GPEM D1 90 Classe D	<b>Mattress</b> Side CPR 21 removable and independant Polyuréthane Ether (300 u)cells of 20 cm therapeutic AIR 4 therapeutic areas : 2 static head celles, 4 cervico-dorsal cells, 10 cells around the sacrum area with air base, 5 heel relief cells Foam wedge  <b>Pump</b> Dimensions : 22 x 25 x 11.5 cm Weight : 2.7 kg technology based on alternating pressure 1 cell in 2 over a complete cycle from 14 to 20 minutes Patented system of automatic and continuous calculation of inflation pressure Comfort adjustment Visual and audible alarms Flow > 8;/min Electrical power supplu : 220 - 240 V - 50 Hz Class II type BF Average consumption 5 Wh Pump decibels: Acoustic pressure according to NF EN3744: <35 dBA Electric and electromagnetic compliance according to the standards IEC 60601-1 Ed.3; IEC 60601-1-2
<b>axtar<sup>®</sup> XXL</b> (pump + overlay) <b>Promust PU HD cover</b> <b>For 140cm wode bed</b>	VAXT/XXL-140	195 x 137 x 20.5 cm			

2 years warrantry

Cleaning instructions: Promust PU HD cover



Attestation of Compliance Technical N°ESC 17-003/2



Brochure for healthcare professionals and service providers.



COMMERCIAL DEPARTMENT

+ 33 (0) 4 66 02 15 15

Web : [www.winnocare.com](http://www.winnocare.com)

MANUFACTURER

WINNOCARE FRANCE

Site Askle Santé

Class 1 MEDICAL DEVICE in accordance with European Directive 93/42/EEC.